

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

*For professional use only*

- **1.1 Product identifier** *For professional use only*
- **Trade name:** Craftmaster Extremely Pink Wood Primer
- **Article number:** 7144
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** *Surface Coating*
- **Application of the substance / the mixture**  
*Surface Coating*  
*Surface Coating*
- **1.3 Details of the supplier of the safety data sheet**
- **Supplier:**  
Craftmaster Paints Ltd  
Academy Works  
Norman Way Ind Est  
Over  
Cambs  
CB24 5QE
- **Further information obtainable from:** Craftmaster
- **1.4 Emergency telephone number:** 01954 231 308

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

STOT RE 2 H373 May cause damage to the central nervous system through prolonged or repeated exposure.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
*The product is classified and labelled according to the CLP regulation.*
- **Hazard pictograms** GHS02, GHS08
- **Signal word** *Warning*
- **Hazard-determining components of labelling:**  
*Solvent naphtha (petroleum), medium aliph.*  
*Hydrocarbons C9-12 N-Alkanes, Isoalkanes Cyclic Aromatics (2-25%)*
- **Hazard statements**  
*Flammable liquid and vapour.*  
*May cause damage to the central nervous system through prolonged or repeated exposure.*  
*Harmful to aquatic life with long lasting effects.*

**Precautionary statements**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Do not breathe dust/fume/gas/mist/vapours/spray.  
Wear protective gloves/protective clothing/eye protection/face protection.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

Contains cobalt bis(2-ethylhexanoate), 2-butanone oxime. May produce an allergic reaction.

**2.3 Other hazards**

**Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

**3.2 Chemical characterisation: Mixtures**

**Description:** Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

|                                      |                                                                                                                                                                                    |         |
|--------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| EC number: 919-857-5                 | Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics,<br><2% aromatics<br>⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336                                           | 2.5-10% |
| CAS: 64742-88-7<br>EINECS: 265-191-7 | Solvent naphtha (petroleum), medium aliph.<br>⚠ Flam. Liq. 3, H226; ⚠ STOT RE 1, H372; ⚠ Asp. Tox. 1, H304;<br>⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336                        | 2.5-10% |
| EC number: 919-446-0                 | Hydrocarbons C9-12 N-Alkanes, Isoalkanes Cyclic Aromatics (2-25%)<br>⚠ Flam. Liq. 3, H226; ⚠ STOT RE 1, H372; ⚠ Asp. Tox. 1, H304;<br>⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336 | 2.5-10% |
| CAS: 136-52-7<br>EINECS: 205-250-6   | cobalt bis(2-ethylhexanoate)<br>⚠ Repr. 2, H361f; ⚠ Aquatic Acute 1, H400; ⚠ Aquatic Chronic 1, H410;<br>⚠ Eye Irrit. 2, H319; ⚠ Skin Sens. 1, H317                                | ≤ 2.5%  |
| CAS: 96-29-7<br>EINECS: 202-496-6    | 2-butanone oxime<br>⚠ Carc. 2, H351; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H312; ⚠ Skin Sens. 1, H317                                                                                | ≤ 2.5%  |

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

**4.1 Description of first aid measures**

**General information:** Immediately remove any clothing soiled by the product.

**After inhalation:** Supply fresh air; consult doctor in case of complaints.

**After skin contact:**

Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing.  
Immediately rinse with water.

**After eye contact:** Rinse opened eye for several minutes under running water.

**After swallowing:**

Do not induce vomiting; call for medical help immediately and show safety datasheet or label.

**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

## **SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**  
*Suitable extinguishing agents:*  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- *For safety reasons unsuitable extinguishing agents:* Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**  
*Protective equipment:* Mount respiratory protective device.

## **SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Prevent seepage into sewage system, workpits and cellars.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**  
Keep receptacles tightly sealed.  
Ensure good ventilation/extraction at the workplace.  
Prevent formation of aerosols.  
Hygiene measures:  
Wash hands before breaks and at the end of workday.  
Use protective skin cream before handling the product.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**  
**Storage:**  
Requirements to be met by storerooms and receptacles: No special requirements.  
Information about storage in one common storage facility: Not required.  
Further information about storage conditions:  
Keep receptacle tightly sealed and in a well-ventilated place.  
Keep away from heat.
- **7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

### - 8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

**136-52-7 cobalt bis(2-ethylhexanoate)**

|     |                                                            |
|-----|------------------------------------------------------------|
| WEL | Long-term value: 0.1 mg/m <sup>3</sup><br>as Co; Carc, Sen |
|-----|------------------------------------------------------------|

**96-29-7 2-butanone oxime**

|     |                                                |
|-----|------------------------------------------------|
| OEL | Long-term value: 1 mg/m <sup>3</sup> , 0.3 ppm |
|-----|------------------------------------------------|

### - DNELs

**Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics,  
<2% aromatics**

|      |      |                  |
|------|------|------------------|
| Oral | DNEL | 300 mg/day (Con) |
|------|------|------------------|

|        |      |                  |
|--------|------|------------------|
| Dermal | DNEL | 300 mg/day (Con) |
|--------|------|------------------|

|  |  |                  |
|--|--|------------------|
|  |  | 300 mg/day (Ind) |
|--|--|------------------|

|            |      |                             |
|------------|------|-----------------------------|
| Inhalative | DNEL | 900 mg/m <sup>3</sup> (Con) |
|------------|------|-----------------------------|

|  |  |                              |
|--|--|------------------------------|
|  |  | 1500 mg/m <sup>3</sup> (Ind) |
|--|--|------------------------------|

**64742-88-7 Solvent naphtha (petroleum), medium aliph.**

|      |      |                 |
|------|------|-----------------|
| Oral | DNEL | 26 mg/day (Con) |
|------|------|-----------------|

|        |      |                 |
|--------|------|-----------------|
| Dermal | DNEL | 26 mg/day (Con) |
|--------|------|-----------------|

|  |  |                 |
|--|--|-----------------|
|  |  | 44 mg/day (Ind) |
|--|--|-----------------|

|            |      |                            |
|------------|------|----------------------------|
| Inhalative | DNEL | 71 mg/m <sup>3</sup> (Con) |
|------------|------|----------------------------|

|  |  |                             |
|--|--|-----------------------------|
|  |  | 330 mg/m <sup>3</sup> (Ind) |
|--|--|-----------------------------|

**Hydrocarbons C9-12 N-Alkanes, Isoalkanes Cyclic Aromatics (2-25%)**

|      |      |                 |
|------|------|-----------------|
| Oral | DNEL | 26 mg/day (Con) |
|------|------|-----------------|

|        |      |                 |
|--------|------|-----------------|
| Dermal | DNEL | 26 mg/day (Con) |
|--------|------|-----------------|

|  |  |                 |
|--|--|-----------------|
|  |  | 44 mg/day (Ind) |
|--|--|-----------------|

|            |      |                            |
|------------|------|----------------------------|
| Inhalative | DNEL | 71 mg/m <sup>3</sup> (Con) |
|------------|------|----------------------------|

|  |  |                             |
|--|--|-----------------------------|
|  |  | 330 mg/m <sup>3</sup> (Ind) |
|--|--|-----------------------------|

- **Additional information:** The lists valid during the making were used as basis.

### - 8.2 Exposure controls

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

- **Respiratory protection:**

When spraying the product, use a respiratory protective device.

If spraying this product, an ABEK respirator to EN141 and EN405 is normally sufficient. If in doubt, consult a respirator manufacturer and show this safety data sheet.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



**Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:**



Tightly sealed goggles

## SECTION 9: Physical and chemical properties

**9.1 Information on basic physical and chemical properties**

**General Information**

**Appearance:**

|                         |                 |
|-------------------------|-----------------|
| <b>Form:</b>            | Liquid          |
| <b>Colour:</b>          | White           |
| <b>Odour:</b>           | Characteristic  |
| <b>Odour threshold:</b> | Not determined. |

|                  |                 |
|------------------|-----------------|
| <b>pH-value:</b> | Not determined. |
|------------------|-----------------|

**Change in condition**

|                                     |               |
|-------------------------------------|---------------|
| <b>Melting point/Melting range:</b> | Undetermined. |
| <b>Boiling point/Boiling range:</b> | 135 °C        |

|                     |       |
|---------------------|-------|
| <b>Flash point:</b> | 29 °C |
|---------------------|-------|

|                                       |                 |
|---------------------------------------|-----------------|
| <b>Flammability (solid, gaseous):</b> | Not applicable. |
|---------------------------------------|-----------------|

|                              |          |
|------------------------------|----------|
| <b>Ignition temperature:</b> | > 200 °C |
|------------------------------|----------|

|                                   |                 |
|-----------------------------------|-----------------|
| <b>Decomposition temperature:</b> | Not determined. |
|-----------------------------------|-----------------|

|                       |                              |
|-----------------------|------------------------------|
| <b>Self-igniting:</b> | Product is not selfigniting. |
|-----------------------|------------------------------|

|                             |                                                                                             |
|-----------------------------|---------------------------------------------------------------------------------------------|
| <b>Danger of explosion:</b> | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
|-----------------------------|---------------------------------------------------------------------------------------------|

**Explosion limits:**

|               |           |
|---------------|-----------|
| <b>Lower:</b> | 0.6 Vol % |
| <b>Upper:</b> | 7.0 Vol % |

|                                  |       |
|----------------------------------|-------|
| <b>Vapour pressure at 20 °C:</b> | 1 hPa |
|----------------------------------|-------|

|                          |                        |
|--------------------------|------------------------|
| <b>Density at 20 °C:</b> | 1.22 g/cm <sup>3</sup> |
|--------------------------|------------------------|

|                         |                 |
|-------------------------|-----------------|
| <b>Relative density</b> | Not determined. |
|-------------------------|-----------------|

|                       |                 |
|-----------------------|-----------------|
| <b>Vapour density</b> | Not determined. |
|-----------------------|-----------------|

|                         |                 |
|-------------------------|-----------------|
| <b>Evaporation rate</b> | Not determined. |
|-------------------------|-----------------|

**Solubility in / Miscibility with water:**

NOT MISCIBLE

|                                                 |                 |
|-------------------------------------------------|-----------------|
| <b>Partition coefficient (n-octanol/water):</b> | Not determined. |
|-------------------------------------------------|-----------------|

**Viscosity:**

|                          |                 |
|--------------------------|-----------------|
| <b>Dynamic at 20 °C:</b> | 250 mPas        |
| <b>Kinematic:</b>        | Not determined. |

|                              |                                            |
|------------------------------|--------------------------------------------|
| <b>Solvent content:</b>      |                                            |
| <b>Organic solvents:</b>     | 17.5 %                                     |
| <b>Solids content:</b>       |                                            |
|                              | 72.7 %                                     |
| <b>9.2 Other information</b> | No further relevant information available. |

## SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**  
No dangerous decomposition products when stored and handled correctly

## SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

### LD/LC50 values relevant for classification:

**Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics**

|        |      |                   |
|--------|------|-------------------|
| Oral   | LD50 | >5000 mg/kg (Rat) |
| Dermal | LD50 | >5000 mg/kg (Rat) |

**64742-88-7 Solvent naphtha (petroleum), medium aliph.**

|            |          |                   |
|------------|----------|-------------------|
| Oral       | LD50     | >5050 mg/kg (rat) |
| Inhalative | LC50/4 h | >13.1 mg/l (rat)  |

**Hydrocarbons C9-12 N-Alkanes, Isoalkanes Cyclic Aromatics (2-25%)**

|            |          |                    |
|------------|----------|--------------------|
| Oral       | LD50     | >15000 mg/kg (Rat) |
| Dermal     | LD50     | >3400 mg/kg (Rab)  |
| Inhalative | LC50/4 h | 13.1 mg/l (Rat)    |

**96-29-7 2-butanone oxime**

|            |          |                                          |
|------------|----------|------------------------------------------|
| Oral       | LD50     | 2326 mg/kg (rat)                         |
| Dermal     | LD50     | 1000 mg/kg (Rab)<br>200-2000 mg/kg (rat) |
| Inhalative | LC50/4 h | >4.8 mg/l (rat)                          |

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure**  
May cause damage to the central nervous system through prolonged or repeated exposure.

- **Aspiration hazard** Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

## SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

## SECTION 14: Transport information

- |                                                                                     |                             |
|-------------------------------------------------------------------------------------|-----------------------------|
| - <b>14.1 UN-Number</b>                                                             |                             |
| - <b>ADR, IMDG, IATA</b>                                                            | UN1263                      |
| - <b>14.2 UN proper shipping name</b>                                               |                             |
| - <b>ADR</b>                                                                        | 1263 PAINT (not viscous)    |
| - <b>IMDG, IATA</b>                                                                 | PAINT                       |
| - <b>14.3 Transport hazard class(es)</b>                                            |                             |
| - <b>ADR, IMDG, IATA</b>                                                            |                             |
|  |                             |
| - <b>Class</b>                                                                      | 3 Flammable liquids.        |
| - <b>Label</b>                                                                      | 3                           |
| - <b>14.4 Packing group</b>                                                         |                             |
| - <b>ADR, IMDG, IATA</b>                                                            | III                         |
| - <b>14.5 Environmental hazards:</b>                                                |                             |
| - <b>Marine pollutant:</b>                                                          | No                          |
| - <b>14.6 Special precautions for user</b>                                          | Warning: Flammable liquids. |
| - <b>Danger code (Kemler):</b>                                                      | 30                          |

|                                                                                  |                                                                                                                                       |
|----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| - <b>EMS Number:</b>                                                             | <i>F-E, S-E</i>                                                                                                                       |
| - <b>Stowage Category</b>                                                        | <i>A</i>                                                                                                                              |
| - <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b> | <i>Not applicable.</i>                                                                                                                |
| - <b>Transport/Additional information:</b>                                       |                                                                                                                                       |
| - <b>ADR</b>                                                                     |                                                                                                                                       |
| - <b>Limited quantities (LQ)</b>                                                 | <i>5L</i>                                                                                                                             |
| - <b>Excepted quantities (EQ)</b>                                                | <i>Code: E1</i><br><i>Maximum net quantity per inner packaging: 30 ml</i><br><i>Maximum net quantity per outer packaging: 1000 ml</i> |
| - <b>Transport category</b>                                                      | <i>3</i>                                                                                                                              |
| - <b>Tunnel restriction code</b>                                                 | <i>D/E</i>                                                                                                                            |
| - <b>IMDG</b>                                                                    |                                                                                                                                       |
| - <b>Limited quantities (LQ)</b>                                                 | <i>5L</i>                                                                                                                             |
| - <b>Excepted quantities (EQ)</b>                                                | <i>Code: E1</i><br><i>Maximum net quantity per inner packaging: 30 ml</i><br><i>Maximum net quantity per outer packaging: 1000 ml</i> |
| - <b>UN "Model Regulation":</b>                                                  | <i>UN 1263 PAINT (NOT VISCOUS), 3, III</i>                                                                                            |

## SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- *Directive 2012/18/EU*
- *Named dangerous substances - ANNEX I None of the ingredients is listed.*
- *Seveso category P5c FLAMMABLE LIQUIDS*
- *Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t*
- *Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t*
- *REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3*
- **National regulations:**
- **Technical instructions (air):**

| <b>Class</b> | <b>Share in %</b> |
|--------------|-------------------|
| <i>I</i>     | <i>0.2</i>        |
| <i>NK</i>    | <i>17.5</i>       |

- *Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.*
- **15.2 Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

## SECTION 16: Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Relevant phrases**
- H226 Flammable liquid and vapour.*
- H304 May be fatal if swallowed and enters airways.*
- H312 Harmful in contact with skin.*
- H317 May cause an allergic skin reaction.*
- H318 Causes serious eye damage.*
- H319 Causes serious eye irritation.*
- H336 May cause drowsiness or dizziness.*
- H351 Suspected of causing cancer.*
- H361f Suspected of damaging fertility.*
- H372 Causes damage to organs through prolonged or repeated exposure.*



*H400 Very toxic to aquatic life.*

*H410 Very toxic to aquatic life with long lasting effects.*

*H411 Toxic to aquatic life with long lasting effects.*

· **Department issuing SDS:** Product safety department: **LABORATORY**

· **Contact:** Health & Safety Officer

· **Abbreviations and acronyms:**

*RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

*ICAO: International Civil Aviation Organisation*

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*IATA: International Air Transport Association*

*GHS: Globally Harmonised System of Classification and Labelling of Chemicals*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*DNEL: Derived No-Effect Level (REACH)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*Flam. Liq. 3: Flammable liquids – Category 3*

*Acute Tox. 4: Acute toxicity – Category 4*

*Eye Dam. 1: Serious eye damage/eye irritation – Category 1*

*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*

*Skin Sens. 1: Skin sensitisation – Category 1*

*Carc. 2: Carcinogenicity – Category 2*

*Repr. 2: Reproductive toxicity – Category 2*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

*STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1*

*STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2*

*Asp. Tox. 1: Aspiration hazard – Category 1*

*Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1*

*Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1*

*Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*

*Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*