



Technical Data Sheet 21.3

October 2016 Revision

Craftmaster PPA Brushing Additive

Craftmaster Paints Ltd, Academy Works, Norman Way Ind Est, Over, Cambs, CB24 5QE

Tel: 01954 231 308 Email: info@craftmasterpaints.co.uk

www.craftmasterpaints.co.uk

Product: Craftmaster PPA Brushing Additive

Sizes Available: 250ml & 1 Litre tins

Colour: Full colour spectrum available

Description: Craftmaster PPA Brushing Additive is a synthetic alkyd resin for prolonging the wet edge time and thus the working window of our top coats and undercoat – with the exception of Anti Slip Deck Enamel, Heat Resistant Paints and Cellulose Paints.

Directions for Use: Add up to 5% in solution to decanted materials (don't add to the tin), as conditions demand.

Excessive use of this additive will lead to reduced dry film thickness which must be taken into account when used. A reduced dry film thickness can lead to a greatly reduced longevity of the final paint finish leading to premature failure.

Do not use for Spraying.

Please Note: It is for the end user to ensure that this product is applied in the correct manner and to the correct standard. Craftmaster Paints Ltd can take no responsibility for faults in paint that is applied in conditions unsuited to painting or paint that has been improperly applied (either the method of application, use of unauthorised additives, insufficient paint build, or other practices which are not conducive to the successful application of our products). We strongly advise all users to consult both our Standard Paint Specification before applying any paint.

This information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials or processes. Such information is to the best of Craftmaster Paints Ltd's knowledge and belief accurate and reliable as of the date indicated. However no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the users responsibility to satisfy themselves as to the suitability and completeness or such information for their own particular use. We recommend this product for professional use only.